

### INTRODUCTIONS

- Effectively control EMI suppression of both line-to-line and line-to-ground noise.
- All part numbers are UL recognized, CSA certified and VDE approved.



### COMPONENTS

PART NO.	C1 (uF)	C2 (uF)	L (mH)	Cy (pF)	R (Ohm)
02DKAG5	0.22	0.22	2.1	3300	2.2M
02DKAW5					
03DKAG5					
03DKAW5					
03DKDG3S					
03DKDW3S					
05DKAG5					
05DKAS5					
05DKAW5					
05DKDG3S					
05DKDW3S					
10DKAG5					
10DKAS5					
10DKAW5					
10DKDG3S					
10DKDW3S					
15DKDG3	0.68X3	—	3.6	10000	200K
* 16DKCG5	0.47	0.47	4.0	10000	330K
20DKBG5	0.22	0.22	1.4	3300	2.2M
20DKBS5	0.22	0.22	1.4	3300	2.2M
30DKCS5	0.22	0.47	0.59	10000	470K

\* DEMKO approved only

PART NO.	Cx (uF)	L (mH)	Cy (pF)	R (Ohm)
03DKBG5B	0.15	2.5	4700	1.0M
03DKBW5B				
06DKBG5B				
06DKBW5B				
12DKBG5B				
12DKBW5B				
16DKCG5B				
16DKCW5B				
20DKCG5B				
20DKCS5B				
30DKCS5B	0.47	0.67	10000	470K

### ELECTRICAL SCHEMATIC



XXDKXX5B

### SPECIFICATIONS

- Maximum leakage current each  
line-to-ground @ 115VAC 60Hz: 0.25mA  
1.0mA (10000pF)  
@ 250VAC 50Hz: 0.45mA  
2.0mA (10000pF)
- Hipot rating (one minute)  
line-to-ground: 2250VDC  
line-to-line: 1450VDC
- Operating frequency: 50/60Hz
- Rated voltage: 115/250VAC

### MINIMUM INSERTION LOSS IN dB






COMMON MODE (L-G) IN 50 OHM SYSTEM							
CURRENT RATING	STYLE	FREQUENCY-MHz					
		.15	.50	1.0	5.0	10	30
2, 3, 5A		22	30	38	47	50	40
3A (S), 5A (S)		22	30	38	50	55	45
10A,10A (S)		15	20	28	45	45	45
15A		20	30	35	45	50	35
16A		25	35	40	45	45	20
20A		14	19	28	40	42	35
30A		10	20	30	40	45	30
DIFFERENTIAL MODE (L-L) IN 50 OHM SYSTEM							
2, 3, 5A		10	46	48	50	50	45
3A (S), 5A (S)		12	46	48	55	50	45
10A,10A (S)		8	38	55	45	45	45
15A		10	40	50	50	50	50
16A		20	50	50	50	40	30
20A		10	35	50	50	45	40
30A		10	30	50	45	35	40

COMMON MODE (L-G) IN 50 OHM SYSTEM							
CURRENT RATING	STYLE	FREQUENCY-MHz					
		.15	.50	1.0	5.0	10	30
3A	BG5B, BW5B	20	30	35	45	50	45
6A	BG5B, BW5B	15	20	25	40	45	45
12A	BG5B, BW5B	10	20	22	35	45	40
16A	CG5B, CW5B	10	18	20	35	45	30
20A	CG5B, CS5B	10	18	20	30	35	35
30A	CS5B	10	25	30	45	50	35
DIFFERENTIAL MODE (L-L) IN 50 OHM SYSTEM							
3A	BG5B, BW5B	7	35	50	45	45	45
6A	BG5B, BW5B	10	20	45	45	50	45
12A	BG5B, BW5B	10	20	40	45	45	45
16A	CG5B, CW5B	10	18	40	40	40	35
20A	CG5B, CS5B	10	12	35	35	40	40
30A	CS5B	12	40	50	50	50	45

**SERIES DIMENSIONS**

CURRENT RATING	STYLE	DIMENSIONS IN INCHES/mm						
		A	B	C	D	E		
2A	AG5	2.99	51.8	0.90	2.38	2.79		
		75.9					22.9	
AW5	1.83	60.5		70.9				
	46.5							
3A	AG5	2.99		1.16			29.5	
		75.9						
	AW5	1.83		0.61	15.5			
		46.5						
	DG3S	3.14		1.29	1.575	0.61		
	DW3S	79.8					32.8	40.01
5A	AG5	2.99		1.16	2.38	2.79		
		75.9					60.5	70.9
	AW5	1.83	0.61	15.5				
		46.5						
	AS5	3.37	1.29	1.575	0.61			
		85.6				32.8	40.01	15.5
DG3S	3.14	1.16	2.38	2.79				
DW3S	79.8				60.5	70.9		
10A	AG5	3.25	2.30	1.29			1.575	0.61
		82.5			58.4	32.8		
	AW5	2.08	1.16	2.38			2.79	
		52.8			60.5	70.9		
	AS5	3.37	1.29	1.575			0.61	
		85.6			32.8	40.01		15.5
DG3S	3.22	2.30	1.29	1.575			0.61	
DW3S	81.5				58.4	32.8		40.01
15A	DG3	4.35	2.22	1.29			1.575	
		110.5			56.4	32.8		40.01
16A	CG5	3.75	2.06	1.54			2.94	
		95.3			52.3	39.1		74.7
20A	BG5	3.25	2.52	1.54			2.94	
		82.5			85.3			
	BS5	3.37				39.1		74.7
		85.6			85.6			
30A	CS5	3.87	2.04	1.54		2.94	3.36	
		98.3			51.8			85.3

**INSERTION LOSS (TYPICAL)**




**SERIES DIMENSIONS**


CURRENT RATING	STYLE	DIMENSIONS IN INCHES/mm									
		A	B	C	D	E	F				
3A	BG5B	2.13 54.00	2.54 64.5	1.34 34.0	1.77 45.0	1.18 30.0	-				
	BW5B						$\frac{3.94}{100.0}$				
6A	BG5B						-				
	BW5B						$\frac{3.94}{100.0}$				
12A	BG5B						-				
	BW5B						$\frac{3.94}{100.0}$				
16A	CG5B						$\frac{2.40}{61.00}$	$\frac{2.81}{71.5}$	$\frac{1.79}{45.5}$	$\frac{2.02}{51.3}$	-
	CW5B						-	$\frac{3.94}{100.0}$			
20A	CG5B						$\frac{2.95}{75.00}$	$\frac{3.34}{84.8}$	$\frac{2.04}{51.8}$	$\frac{2.52}{64.0}$	-
	CS5B						-	-			
30A	CS5B	$\frac{4.06}{103.00}$	$\frac{4.49}{114.0}$	$\frac{2.22}{56.5}$	$\frac{3.74}{95.0}$	$\frac{1.83}{46.4}$	-				

**MECHANICAL CONSTRUCTION**

AG5



AW5



ALL WIRE LEADS 4.0" LONG MIN.


UNIT:  $\frac{\text{INCH}}{\text{mm}}$



**MECHANICAL CONSTRUCTION**




DG3



SUGGESTED MOUNTING CUTOUT



DW3S




SUGGESTED MOUNTING CUTOUT (SAME AS ABOVE)


ALL WIRE LEADS 4.0" LONG MIN.




BG5B, BW5B  
(option wire style)



CG5B




CW5B



ALL WIRE LEADS 4.0" LONG MIN.



CS5B



UNIT:  $\frac{\text{INCH}}{\text{mm}}$