




[Products](#) [Documentation](#) [Resources](#) [My Account](#) [Customer Support](#)

**SLSA1201 Product Details**

[Live Product Chat](#)



**SLSA1201**  
(5-1437577-4)  
TE Internal Number: 5-1437577-4  
 [Superseded](#)  
[Search for Replacement Parts](#)

**Slide Switches**

[Not EU RoHS or ELV Compliant \(Find RoHS Compliant Alternates\)](#)

**Product Highlights:**

- Number of Positions = 2
- Single Pole - Double Throw Configuration (Pole-Throw)
- Actuator Style = Top
- Actuator Color = Black
- SLSA Series

[View all Features](#)

**Quick Links**

- ▶ [Check Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

[Add to My Part List](#) [Request Sample](#)

[Find Similar Products](#)

Documentation & Additional Information	
<p><b>Product Drawings:</b></p> <ul style="list-style-type: none"> <li>● None Available</li> </ul> <p><b>Catalog Pages/Data Sheets:</b></p> <ul style="list-style-type: none"> <li>● <a href="#">ALCOSWITCH PRODUCTS</a> (PDF, English)</li> </ul> <p><b>Product Specifications:</b></p> <ul style="list-style-type: none"> <li>● None Available</li> </ul> <p><b>Application Specifications:</b></p> <ul style="list-style-type: none"> <li>● None Available</li> </ul> <p><b>Instruction Sheets:</b></p> <ul style="list-style-type: none"> <li>● None Available</li> </ul> <p><b>CAD Files:</b></p> <ul style="list-style-type: none"> <li>● None Available</li> </ul>	<p><b>Additional Information:</b></p> <ul style="list-style-type: none"> <li>● <a href="#">Product Line Information</a></li> </ul> <p><b>Related Products:</b></p> <ul style="list-style-type: none"> <li>● <a href="#">Tooling</a></li> </ul>

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)	
<p><b>Product Type Features:</b></p> <ul style="list-style-type: none"> <li>● <a href="#">Number of Positions</a> = 2</li> <li>● Configuration (Pole-Throw) = Single Pole - Double Throw</li> <li>● Actuator Style = Top</li> <li>● Mount Angle = Vertical</li> <li>● Grade = Consumer</li> <li>● Termination Type = Turret</li> </ul> <p><b>Electrical Characteristics:</b></p> <ul style="list-style-type: none"> <li>● Contact Rating = 200mA @ 12 VDC, 500mA @ 125 VAC</li> </ul> <p><b>Body Related Features:</b></p> <ul style="list-style-type: none"> <li>● Actuator Color = Black</li> <li>● Series = SLSA</li> <li>● Mount Style = Through-Hole</li> <li>● PCB Tail Length (mm [in]) = 3.30 [0.130]</li> <li>● Actuator Length (mm [in]) = 3.20 [0.126]</li> <li>● Actuator Material = Phenolic</li> </ul>	<p><b>Contact Related Features:</b></p> <ul style="list-style-type: none"> <li>● Contact Plating = Silver</li> <li>● Contact Material = Copper Alloy</li> </ul> <p><b>Configuration Related Features:</b></p> <ul style="list-style-type: none"> <li>● Terminal Configuration = Standard</li> <li>● Number of Actuators = Single</li> </ul> <p><b>Industry Standards:</b></p> <ul style="list-style-type: none"> <li>● <a href="#">RoHS/ELV Compliance</a> = Not ELV/RoHS compliant</li> <li>● <a href="#">Lead Free Solder Processes</a> = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C</li> </ul> <p><b>Identification Marking:</b></p> <ul style="list-style-type: none"> <li>● Stamped Marking = With</li> </ul> <p><b>Other:</b></p> <ul style="list-style-type: none"> <li>● Brand = Alcoswitch</li> </ul>

[Provide Website Feedback](#) | [Need Help?](#)